

Products under development

Model	Description	Sample Available	Safety Approval
PLM-12E/25E	12W/25W economical LED power supply with PFC, C.C. mode, 180~295Vac, Class II design (no F.G.), plastic case, clamp style I/O, no load power consumption <0.5W	2015.02	2015.02
GST90A	90W Industrial Green Adaptor with PFC function, no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.03	2015.03
GST120A	120W Industria Green Adaptor with PFC function, no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.03	2015.03
OWA-60 (U/E type)	60W moistureproof adaptor , no load power consumption<0.15W (ErP ,EISA 2007/DoE Level VI) , Class II design(no F.G)	2015.04	2015.04
OWA-120 (U/E type)	120W moistureproof adaptor , no load power consumption<0.15W (ErP ,EISA 2007/DoE Level VI) , Class II design(no F.G)	2015.04	2015.04
NPF-120(D)	120W LED power supply with PFC, Class II design(no F.G.), plastic case, potted, 277VAC input available, no load power consumption<0.15W (<0.5W for D type) ,IP67,built-in 3 in 1 dimming function for D type	2015.04	2015.04
PWM-120	120W LED power supply with PFC, PWM style output , Class II design (no F.G.),plastic case, potted, 277VAC input available, no load power consumption<0.5W,IP67,built-in 3 in 1 dimming function	2015.04	2015.04
GSC18 (B/E type) GSC25 (B/E type) GSC40 (B/E type)	18W/25W/40W LED power supply with PFC function (adaptor style) , C.C. mode , no load power consumption<0.15W , 277VAC input available , Class II design(no F.G)	2015.04	2015.04
PLM-40E	40W economical LED power supply with PFC, C.C. mode, Class II design (no F.G.), plastic case, clamp style I/O, 277VAC input available, no load power consumption <0.15W	2015.04	2015.04
IRM-45/60	45W/60W industrial encapsulated type(3.43"*2.05" compact size) , no load power consumption<0.1W	2015.04	2015.04
GST40A/60A	40W/60W Industria Green Adaptor, no load power consumption <0.075W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.04	2015.04

LPC-100	100W economical LED power supply(plastic case) , C.C. mode , non PFC , Class II design(no F.G)	2015.05	2015.05
NDR-240	240W economical slim DIN rail power supply(width:63mm) , PFC function	2015.05	2015.05
NDR-480	480W economical slim DIN rail power supply(width:85.5mm), PFC function	2015.05	2015.05
APV/C-08	8W econormical LED power supply(plastic case) , non-PFC , C.C. mode for APC-08 , C.V. mode for APV-08	2015.05	2015.05
GST280A	280W Industria Green Adaptor with PFC function, no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.05	2015.05
GST18 (B/E/U) GST25 (B/E/U) GST36 (B/E/U)	18W/25W/36W Industria Green Adaptor , no load power consumption <0.075W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.06	2015.06
GST160A	160W Industria Green Adaptor with PFC function, no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.06	2015.06
GST220A	220W Industria Green Adaptor with PFC function, no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.06	2015.06
HEP-100/150/185	100W/150W/185W harsh environment power supply , matal case , potted , 10G vibration , -55~+70°C, 6kV surge immunity level , fanless design	2015.06	2015.06
ELG-150-C ELG-150-V	150W economical LED power supply with PFC, metal case, potted, 180~295Vac, C.C. mode for ELG-150-C , C.V mode for ELG-150-V , no load power consumption <0.5W , smart dimming function	2015.06	2015.06
GSM160B	160W Medical Green Adaptor with PFC function, Class II design(no F.G.), no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.07	2015.07
GSM220B	220W Medical Green Adaptor with PFC function, Class II design(no F.G.), no load power consumption <0.15W (EISA 2007/DoE Level VI, NRCan, AU/NZ MEPS, EU ErP and CoC Version 5)	2015.07	2015.07
PLV-12/25/40	12W/25W/40W economical LED power supply with PFC, C.V. mode, Class II design (no F.G.), plastic case, clamp style I/O, 277VAC input available, no load power consumption <0.5W	2015.07	2015.07
IDL-45	45W economical LED power supply with PFC, C.C. mode, Class II design (no F.G.), low profile plastic case, clamp style I/O, 180~295Vac, no load power consumption <0.5W , built-in 2 in 1 dimming	2015.07	2015.07

HLG-240H-C	240W LED power supply with PFC, C.C. mode(>60VDC), metal case, potted, 277VAC input available, IP67/IP65, built-in 3 in 1 dimming	2015.07	2015.07
ELG-100-C ELG-100-V	100W economical LED power supply with PFC, metal case, potted, 180~295Vac, C.C. mode for ELG-100-C , C.V. mode for ELG-100-V, no load power consumption <0.5W , smart dimming function	2015.07	2015.07
IDL-25	25W economical LED power supply with PFC, C.C. mode, Class II design (no F.G.), low profile plastic case, clamp style I/O, 180~295Vac, no load power consumption <0.5W , built-in 2 in 1 dimming	2015.08	2015.08
HEP-240	240W harsh environment power supply , metal case , potted , 10G vibration , -55~+70°C, 6kV surge immunity level , fanless design	2015.08	2015.08
HEP-320	320W harsh environment power supply , metal case , potted , 10G vibration , -55~+70°C, 6kV surge immunity level , fanless design	2015.08	2015.08
IDL-65	65W economical LED power supply with PFC, C.C. mode, Class II design (no F.G.), low profile plastic case, clamp style I/O, 180~295Vac , no load power consumption <0.5W , built-in 2 in 1 dimming	2015.09	2015.09
ELG-240-C ELG-240-V	240W economical LED power supply with PFC, metal case, potted, 180~295Vac, C.C. mode for ELG-240-C , C.V. mode for ELG-240-V, no load power consumption <0.5W , smart dimming function	2015.09	2015.09
ELG-75-C ELG-75-V	75W economical LED power supply with PFC, metal case, potted, 180~295Vac, C.C. mode for ELG-75-C , C.V. mode for ELG-75-V, no load power consumption <0.5W , smart dimming function	2015.10	2015.10