



Excellent Performance LED Drivers



Compact Size
as small as a business
card holder

XLG Series

3 in 1
Dimming

IP67

5
Years
Warranty

25W / 50W / 75W / 100W / 150W / 200W / 240W

- Constant Power Mode design LED driver
- Universal input 100~305V AC(Class I)
- India EESL version (optional)
- AC/DC Cable with global certificate
- Surge protection: 6kV/4KV. (10KV/6KV optional)
- Latest safety requirements of IEC 61347/GB7000.1 and UL 8750, dimming circuit with isolation
- IEC 61347 independent control gear application

www.meanwell.com

M + R
Multitronik GmbH


powerful (l) support

Your Distributor:

M+R Multitronik GmbH
Grootkoppel 16 • 23858 Reinfeld
Tel. +49 4533 6063-200
info@multitronik.com
www.multitronik.com

Model Encoding

XLG - 150 I - L -



Function mode options, as advised in the following table
 Rated Output Voltage (12/24V or L/M/H types)
 I : for India version
 : for standard version
 Output wattage (25/50/75/100/150/200/240W)
 Series name

Type	Function	Note
Blank	Io and Vo fixed. (For harsh environment)	By request
A	Io adjustable via built-in potentiometer	In stock
AB	Io adjustable via built-in potentiometer and 3 in 1 dimming function (0~10Vdc, 10V PWM signal and resistance)	In stock

Note: 12V and 24V models without AB type.

Applications

- ✓ Skyscraper lighting
- ✓ Street lighting
- ✓ Floodlight lighting
- ✓ Stage lighting
- ✓ Fishing lighting
- ✓ Horticulture lighting
- ✓ Bay lighting
- ✓ Type HL for use in class I
- ✓ DMX power supply

XLG Series Family Table

Output Mode	12V	24V	L Type	M Type	H Type (56V)	Dimension (mm)
XLG-025W	X	X	X	X	250~1050 mA	105x63x30
XLG-050W	X	X	X	X	530~2100 mA	105x63x30
XLG-075W	5A	3.1A	700~1050 mA	X	1300~2100 mA	140x63x30
XLG-100W	8A	4A	700~1050 mA	X	1750~2700 mA	140x63x30
XLG-150W	12.5 A	6.25A	700~1050 mA	1400~2100 mA	2680~4100 mA	180x63x35
XLG-200W	16 A	8.3A	700~1050 mA	X	3500~5500 mA	199x63x35
XLG-240W	18A	10A	700~1050 mA	1400~2100 mA	4280~6600 mA	219x63x35

X: Not available